

PAWELL

CRANE SCALE



PRODUCT FEATURES

- Capacity up to 30t
- Durable and high-strength parts
- Aluminum die-casting enclosure
- LED display with backlight
- American standard bow shackle and eye Hook
- Auto accumulation, long distance tarring, Overload alarm.

PRODUCT FEATURES

Accuracy class: OIML III Grade
 Operation time: 60 hours
 Safe over load: 150%FS
 Working temperature range: -10~50°C
 Operation Humidity: <95% RH
 Dimension of Display: 5 digits 30mm (1.2") LED
 Stability time for reading: <5.0 Second



Crane scale 1t- 10t

Crane scale 15t- 30t

CAPACITY AND DIVISION

Model	Capacity (ton)	Division (kg)	Length (mm)	Ring radian (mm)	Ring width (mm)	Lifting hook (mm)	Weight (kg)
CS01	1	1	505	95	58	35	11.5
CS02	2	1	505	95	58	35	11.5
CS03	3	1	505	95	58	35	11.5
CS05	5	2	610	120	80	45	16.4
CS10	10	5	650	125	90	45	21
CS15	15	5	940	135	98	55	45.5
CS20	20	10	1100	235	127	70	73.5
CS30	30	10	1290	335	145	90	98